## FC-BOX17-1165G7



Fanless system without cooling fan, no any noise, thicker and longer heat-sink


3xStorage: 1xMSATA SSD+1xM.2 NVME SSD+1x2.5"SATA installation together;


- Fit for 9-36V 3pin phoenix terminal power input, ATX/AT quick switch.
- Support VGA + HDMI dual display output synchronously.
- One embedded SIM card slot onboard for 3G/4G Wi-Fi.
- Support Watchdog, AWAL, RTC, WOL(ATX mode), PXE, Reset functions.
- Low consumption TDP only 10W and can be mounted on the wall.














u	

CPU	Intel Core i7-1165G7, 4 Cores, 8 Threads, B Turbo 4.7GHz, Fanless	ase 2.8GHz,
Memory	8/10/11gen 2xDDR4 SODIMM	
Storage	1x SATA3.0 Slot 1x M.2 2280 M KEY PCIE3.0 1x mSATA slot	
Network	2 x GbE RJ45 Intel i211/i210	
I/O	4x USB3 0 + 2x USB2 0 2x RS232 COM + 4x RS232/485/422 COM 1x PS2 14x GPI0 (7 input, 7 output) Power, Reset and Clear CMOS Buttons	3pin Power phoenix Support: 9-36V DC 3.5mm Audio Jack Mic in 1x ATX/AT 2x Antenna port for WIFI/3G/4G
Video	Intel UHD Graphics 620 for 8th CPU 1x HDMI 4096x2304@30Hz(4K) 1x VGA 1920x1080@60Hz(1080P)	
Expansion Slot	1x Mini-PCle half card, support WIFI Bluetooth1x Mini-PCle full card (with SIM card holder), support 3G/4G module, WIFI Bluetooth1x Expand IO, support LPC, USB, PCIE	
Operation	Windows® 7/8/10/11, WES 7/10, LINUX	

## **POWER SUPPLY**

External Power Supply	А

C 100 - 240V

DC 9-36V Working voltage

**ENCLOSURE** 

Material Aluminum Allov Color Black

## **OPERATING ENVIRONMENT**

Operating: -20 to 70°C, Storage: -30 to 80°C, surface air flow Temperature Range

10%~95%, non-condensing Relative humidity

PACKING DETAILS	
Net weight	2.2 kg
Gross weight	3.5 kg
Product Dimension	249 x 150 x 86 mm
Accessories	Power adapter, Driver CD, 2.5-inch hard drive bracket, Screws
Packing size	300 x 200 x 120 mm

## **OTHER**

Mounting (options)

Wall mounting Embedded mount

